



HOT FEED

IMPORTANT PRODUCT INFORMATION

New

24 Volt Circuit Breakers

Integral mounting bracket with stud terminals.

Snap-in bracket mounting with stud terminals.



Type I Circuit Breakers
Cycle or continuously "re-set" until the overload is corrected.
Conform to SAE recommended practice J 553C.



- Plated steel case and bracket.
- Two #10-32 stud terminals with hex nuts and lock washers supplied.
- Dimensions: 2.0"L x .78"W x 1.37"H (50.80mm x 19.81mm x 34.97mm).
- Two .22" (5.61mm) mounting holes, 1.56" (39.62mm) on center.

- Plated steel case.
- Two #10-32 stud terminals with hex nuts and lock washers supplied.
- Dimples stamped in case provide secure anchorage for snap-in bracket mounting.
- Dimensions: 1.25"L x .78"W x 1.33"H (31.75mm x 19.81mm x 33.78mm).

Amps	Part No.
10	30172-10
15	30172-15
20	30172-20
30	30172-30

Amps	Part No.
10	30171-10
15	30171-15
20	30171-20
30	30171-30

Mounting brackets for No. 30171 series circuit breakers:
30090 Series: steel construction, 2 through 8 gangs.
81728 Series: nylon construction, 4 through 13 gangs.
86126 Series Bus Bars: for use with 81728 series brackets.

CH Cole Hersee Co.

20 OLD COLONY AVENUE, SOUTH BOSTON, MA., U.S.A. 02127-2467
Telephone (617) 258-2100 • Telex 94-0901 • FAX (617) 258-9490

Form No. D-547