

# HOT FEED

Information on New Products from Cole Hersee Company

## **NEW** LED Pilot Lights

- Solid-state light-emitting diode never needs replacement
- Clean, attractive design matches any panel
- Bright chrome-plated body, bezel, washer and hexnut
- Bezel protects LED from damage, and reflects more light



Mounting hole: 0.546" diameter (13.9mm).

Quick connect 0.250" (6.4mm) terminals are polarized for ease of wiring.

Body length: 1.248" (31.7mm), maximum bezel diameter 0.630" (16.0mm).

Fits into panels 0.020" through 0.300" thick (0.5 to 7.6mm).

PL-612-R red lens, 12V

PL-612-G green lens, 12V

PL-612-B blue lens, 12V

PL-612-A amber lens, 12V

Also available in 24V version by special order (PL-624 series).

## Warning Devices



### 40212 Universal Buzzer 12V DC

Utilizes advanced integrated circuit surface mount technology. Negative ground. Use with two input sources to warn of two different hazardous conditions. Sounds at two different rates: one sensor triggers a fast-rate alarm, the second actuates a slower rate alarm tone. Minimum sound level: 90dB. Lightweight molded plastic housing. Solid-state circuitry.



### 4099 Universal Buzzer 12V DC

Hundreds of uses. For 'door ajar' warning, bus driver alert, low air pressure, temperature, etc. Works with any temperature, pressure, door or momentary switch. Electrical contacts are designed for instant response and uninterrupted signal.

Impact-resistant ABS resin case. Moisture-repellent insulator. Two screw terminals with lockwashers. Size: 1 7/32" L x 2 1/2" W x 2 1/32" H (30.9 x 63.2 x 64.3mm).



### 4112-RC Pilot Light Buzzer 12V DC

Rugged combination warning light and buzzer give audible and visible alert. Universal application: use with any electrical switch. Red lens, long-life LED. 1/16" (17.46mm) diameter mounting stem, 1/32" (13.88mm) long. Body size: 1 7/8" L x 1" W x 1 1/32" H (47.6 x 25.4 x 34.1mm).

Wiring instructions provided. 12V DC. Also available as 24V. Item No. 4124-RD.



## Cole Hersee Co.

20 Old Colony Avenue, Boston, MA USA 02127-2467 • (617) 268-2100 • Fax (617) 268-9490

See our interactive product catalog at [www.colehersee.com](http://www.colehersee.com)

All specifications and information is subject to change without notice.